

# Trimline 73H Tunnel

A TUNNEL FIREPLACE IS ALL ABOUT ELEGANCE,  
AND OUR TRIMLINE 73H TUNNEL EVEN MORE SO.



A tunnel fireplace is all about elegance. Provided your space is suited to it, it's a beautiful way to divide rooms. The Trimline 73H Tunnel was designed with extra height in mind, adding even more warmth and charm to your space.

The standard version of this fireplace has a burner bed made of wooden logs and is equipped with a double burner. This burner creates a beautiful interplay of flames while limiting the amount of heat generated. On top of that, it comes with the

Ecomax remote control and you have the options of adding Wi-Fi-control with our Trimline Fires app.

## Product specifications

### FEATURES

- Balanced flue gas fire
- Tunnel model
- Double burner
- Wood logs fuel bed
- Ecomax remote control
- Antracite steel panel interior

### OPTIONALS

- Pebbles fuel bed
- Anti reflective glass
- Wide trims
- Mains adapter GV60
- Wall bracket remote control
- Domotica smart connection
- Wall switch
- Wi-Fi remote app control
- Puck control

## Styling & Optionals

### Ecomax remote control

For absolute ease of use all appliances are supplied with an Ecomax remote system that controls the fire at the touch of a button.



### Options interior finish materials and Trimline Wi-Fi control

For that extra WOW factor, there is also an option to upgrade to anti-reflective glass. Other available upgrades also include Wi-Fi and pebbles burner bed.





|                                 |   |                           |                           |                         |
|---------------------------------|---|---------------------------|---------------------------|-------------------------|
| Appliance name                  | Trimline 73H Tunnel   |                           |                           |                         |
| Appliance type                  | Balanced flue built-in gas fires (C11, C31, C91)  |                           |                           |                         |
| Purpose                         | Ambient heating, real flames  |                           |                           |                         |
| Engine identification           | 1152 (T)  |                           |                           |                         |
| Gas type-pressure               | Natural gas G25.3 – 25 mbar   | Natural gas G20 – 20 mbar | Natural gas G25 – 20 mbar | LPG G30/31 – 28-50 mbar |
| Heat input (kW)                 | 11,0  | 11,4                      | 9,4                       | 9,3                     |
| Heat output max (kW)            | 9,8   | 10,1                      | 8,4                       | 7,9                     |
| Heat output min (kW)            | 2,7   | 3,1                       | 2,5                       | 2,6                     |
| Consumption (m³/h and kg/h LPG) | 1,3   | 1,2                       | 1,16                      | 0,5                     |
| Efficiency (%)                  | 89  | 89                        | 89                        | 85                      |
| Energy label highest efficiency | A   | A                         | A                         | B                       |
| Flue lay out wall termination   | Indirect 1m vertical and max 5,5m horizontal  |                           |                           |                         |
| Weight (kg)                     | 150   |                           |                           |                         |
| Efficiency class EN613          | 1   |                           |                           |                         |
| NOx Class                       | 5   |                           |                           |                         |
| PIN ID CE                       | 0461CQ1048  |                           |                           |                         |
| Gas connection                  | 3/8" outside connection   |                           |                           |                         |
| Electrical connection           | 6 VDC battery powered   |                           |                           |                         |
| Gas control system              | Mertik Maxitrol SYMAX B6R radio controlled 866 mHz  |                           |                           |                         |
| Safety                          | Thermocouple flame supervision and pressure hatches   |                           |                           |                         |
| Heat distribution               | Internal convection system  |                           |                           |                         |
| Connectivity                    | Optional App control (Android and IOS), wall switch and domotica connection                         |                           |                           |                         |
| Flue type and diameter          | Holetherm-CC concentric flue 130-200mm  |                           |                           |                         |
| Standard supplied               | Adjustable legs – Convection chamber and grills – Wall brackets – Log set                           |                           |                           |                         |
| Optional                        | Wide trims  |                           |                           |                         |
| Remarks                         | Always use non-combustible construction materials such as metal stud framing and fireboard cladding |                           |                           |                         |

## Installation details

### Concentric flue system

Using the THC-CC double wall chimney system the flue gases are safely transported to the outside and fresh combustion-air is pulled inside the appliance. Balanced flue appliances can be installed using a wall terminal so no traditional chimney is needed. THC-CC is made of high quality stainless steel and approved according CE standards in combination with the Trimline appliances.



### Balanced flue gas fire

One of the most innovative aspects of the Trimline 73H Tunnel is that there is no need for an existing chimney to be present. This is all down to the clever features of our balanced flue gas fire, that is fully room sealed. Not only does this make for a highly efficient and safe appliance, but when combined with our concentric flue system, our fires can be positioned in virtually any part of your home with a relatively simple 'chimney breast' built around it. A direct wall outlet from the back of the fire makes the installation even easier.